

## SPECIFICATIONS

MODEL	GALLON CAPACITY	NET STORAGE CAPACITY	INPUT BTU/HR NATURAL & LP GAS	TEMP. RISE IN DEGREES FAHRENHEIT		FIRST HOUR RATING	THERMAL EFFIC. %	SOLAR EXCHANGE SQUARE FEET	VENT SIZE	HEIGHT	WIDTH	DEPTH	SHIP WEIGHT
PHS199-119	119	61	199,000	100		335	97%	13.5	3"	74"	27-1/4"	46"	425 lbs
				GPH GPM	363 6								
PHS199-80	80	41	199,000	GPH GPM	363 6	300	96%	13.5	3"	72"	23-1/4"	36"	255 lbs
PHS130-119	119	61	130,000	GPH GPM	236 3.9	250	97%	13.5	2"	74"	27-1/4"	46"	425 lbs
PHS130-80	80	41	130,000	GPH GPM	236 3.9	220	96%	13.5	2"	72"	23-1/4"	36"	255 lbs

Recovery on rating plate is based at 96% thermal efficiency at 100 degrees Fahrenheit rise, as required by A.N.S.I.

CONNECTION SIZES ARE 1-1/2" NPT DOMESTIC CONN., 1" NPT HEATING CONN., 1" FIP SOLAR CONN.

Heat Transfer Products reserves the right to change specifications or discontinue models without notice.